



SOFT-WALL & MACHINE PROTECTION SOLUTIONS

Product Specification

Part #: 01-17-1016

Description: IW, SINGLE BATTING, PREMIUM

Product Applications:

Used in applications separating up to 15°F

Thermal resistance: R- 3

General applications include: freezer to freezer, freezer to cooler or cooler to cooler

Other applications possible upon engineering review

Product Design:

ASTM E-84 class A exterior vinyl

High tear resistant and puncture resistant 18oz vinyl exterior

Recycled polyester batting insulation

Product Construction:

Flexible partitions are 5' wide continuous height panels

Binding sewn on edges and top of panels

Impact relief double folded vinyl with Velcro tab to minimize panel separation

Cut slope on all panels to accommodate roof pitch

Heavy duty #4 grommets every 12" along the top of panels. Adjustable and replaceable bottom sweep enclosed inside panels on double Velcro

Valance for bar joist area cut to height, all edges closed with binding, heavy duty #4 grommets every 12" top and bottom

Approval and installation drawings provided with each order

Weight – 0.34 lbs/sqft

Available Options:

Strip doors (ribbed, reinforced, low temperature)

Mounting angle (galvanized, aluminum)

Factory cut door openings with grommets every 12" top and sides

Clear vision panels

Disclaimer: End user is responsible for checking with local fire department and/or insurer prior to installation of curtains to ensure compliance with all fire regulations.

Part #: 01-17-1016
 IW, SINGLE BATTING, PREMIUM

